

STATE OF CALIFORNIA Department of General Services - Office of Procurement

PURCHASE ORDER

Purchase Order No. Rev. Date 62327 4/ 1/2009

Supplier No. Solicitation No. Delivery Date F.OB Point Invoice Terms 670839 57181 90 Days ARO Destination

Form GSOP 1-PIN (04/98)

THORSON GMC-BUICK MOTOR CO. 3456 E COLORADO BL PASADENA, CA 91107 Attn: STEPHEN V. CERNI

DEPT OF MENTAL HEALTH h T METROPOLITAN ST. HOSPITAL 11401 BLOOMFIELD AVENUE NORWALK, CA 90605

9ENERAL SERVICES Z-01 a T REAL ESTATE SVS DIVISION 707 3RD ST, STE 3-305 WEST SACRAMENTO, CA 95605

Agency Billing Agency Purchase Estimate Purchase Estimate 30331 3124234 67326 Agency Contact Phone Date Received

Phone: 626-795-8851

KATHY VESTAL

916-376-1649

Unit Price Extension Quantity Commodity Description Item No. Code

THE GENERAL PROVISIONS FOR NON-IT COMMODITIES ARE HERBY INCORPORATED BY REFERENCE. THESE GENERAL PROVISIONS CAN BE OBTAINED BY PHONING (916) 375-4400 OR BY ACCESSING OUR WEBSITE AT:

www.documents.dgs.ca.gov/pd/model1ang/GPnonIT0407.pdf

THE FOLLOWING INFORMATION IS PROVIDED FOR AGENCY USE ONLY:

PRIME CONTRACTOR: NS

2320-009-0434-1 TRUCK REFRIGERATOR Van, Refrigerated, 26' with Liftgate as described meeting the requirements of the attached specification #2320-0501 of three (3) pages, dated 11/17/2008.

89.600.9500

268,802.85

Brand: GMC Model: 2010 TC7C042

Total Value:

268.802.85

FOB DESTINATION:

For the purpose of this order, only F.O.B. Destination will be accepted.

AUTHORIZED DISTRIBUTOR/DEALER:

Authorized distributor/dealer must be listed in the manufacturers written or electronic list of distributors if such a list exists. An "AUTHORIZED DISTRIBUTOR/DEALER" should have documentation or a signed agreement from the manufacturer indicating its status as "FACTORY AUTHORIZED" these documents must be made available to the State upon request. A "ONE-TIME" agreement is not acceptable.

Sales and/or use tax to be extra unless noted above

Buver Phone **BOC** Number 916-375-4499

PURCHASE ORDER CONTINUATION

Form GSOP 2-PIN (04/98)

Purchase Order No.	Revision	Date	Supplier No.	Supplier Name	7
62327	· ·	4/ 1/2009	670839	THORSON GMC-BUICK MOTOR CO.	١

Item No. Quantity Unit Commodity Code Description Unit Price Extension

VEHICLE REGISTRATION DOCUMENTS REQUIRED:

The original dealers: Report of Sale" shall be furnished by all California licensed dealers at the time of delivery of the unit covered by these specifications. An original weight cerificate from a California certified Weigh Master for registration purposes shall be supplied at the time of delivery. a Federal Excise Tax Exempt Certificate will be attached to the purchase order.

INSPECTION REQUIREMENT:

Vehicle will be inspected for compliance with these specifications by a Department of General Services Inspector of Automotive Equipment at the dealer's place of business prior to delivery. It will be responsibility of the dealer to ask for inspection when vehicle is ready for for delivery. The burden of proof of compliance with this specification will be the responsibility of the bidder.

WARRANTY:

The system shall be fully warranted by the successful bidder to be free from defects in materials (except consumables) and workmanship for a period of one year from date of acceptance. If the manufacturer's warranty on the described unit is greater than one year, then the warranty will be extended to the State.

OPERATING MANUAL:

One copy of the operating manual, service manual, and parts book shall be furnished at the time of delivery. If there are any special tools required for normal operation, one set shall be provided. All manuals and instructions shall be in the English language.

CALIFORNIA VEHICLE CODE: *

California Vehicle Code: Bidders shall comply with all provisions of the Code pertaining to occupational licensing requirements for vehicle dealer, manufacturers, etc. Bidders are to submit (with the bid or within 5 days of request) a copy of their valid occupational license issued by the California Department of Motor Vehicles, or a valid copy of their dealer's license issued by the state where their business is located along with a copy of the occupational license of the California joint bidder. Bidders who fail to submit a copy of a valid occupational license when requested will not be eligible for award.

DOCUMENTS:

The following documents shall be delivered to the consignee (receiving agency) with the vehicle:

- Completed and Signed Pre Delivery Inspection Checklist, including the P.O. Number and Vehicle I.D.
- "Line Set Tickets" or "Window Sticker" showing all options installed. PRE DELIVERY CHECK LIST:

Prior to delivery, the vehicle shall be completely inspected and serviced by the delivering dealer and/or the manufacturer's pre-delivery service center. A copy of of the pre-delivery service checklist shall be completed for each vehicle, signed by a representative of the organization performing the inspection/service delivered with the vehicle.

All deliveries shall be made during normal business hours 8:00 to 5:00 P.M., Monday thru Friday, except for State Holidays.

Page 2

STATE OF CALIFORNIA

Department of General Services - Office of Procurement

PURCHASE ORDER CONTINUATION

Form GSOP 2-PIN (04/98)

Page 3 (Last)

Purchase Order No.	Revision	Date	Supplier No.	Supplier Name
62327		4/ 1/2009	670839	THORSON GMC-BUICK MOTOR CO.

Item No.	Quantity	Unit	Commodity Code	Description	Unit Price	Extension

RECEIVING/INSPECTION:

Vehicles will be inspected for compliance with these specifications by a State inspector at the dealer's place of business prior to delivery. Inspection will commence within five (5) working days of notification. Inspection will include: specification compliance, workmanship, appearance and proper operation of all equipment and systems and that all documents are present. The burden of proof of compliance with this specification will be the responsibility of the bidder. Call the agency contact reference on the Purchase Order for assistance in contacting the State inspector.

Completion of inspection or acceptance by the State inspector shall in no way release the dealer\from satisfying the requirements of the contract, specifications, and warranty. Deviations from the specified requirements that are detected by the owning agency shall be corrected by the dealer in an expeditious manner at no expense to the owning agency.

Preparation for Delivery: The completed vehicle as presented for the "final" acceptance shall be cleaned, internally and externally (freshly washed and chamois) and delivered full of fuel and with a full charge to the battery system.

Parts and Service: Body and component repair parts and service shall be readily available from the contractor.

Weight Certificate: Upon delivery, (for registration purposes) the contractor must provide a certified weight certificate showing the total "Tare" weight for the vehicle.

CHANGE ORDERS:

This Purchase Order may be amended, modified, or terminated at any time by mutual agreement of the parties in writing. Change orders amending, modifying or terminating the Purchase Order, including any modifications of the compensation payable, may be issued only by the State Procurement Officer. All such change orders shall be in writing and issued only upon written concurrence of the supplier. Termination, as that term is used in this section, does not include termination for default of the supplier.

This Purchase order has been registered into the state contact and procurement registration system (https://www.scprs.dgs.ca.gov/). The registration number is eP 1002154.



STATE OF CALIFORNIA BID SPECIFICATION VAN, REFRIGERATED, 26' WITH LIFTGATE

2320-0501

1 SCOPE

This specification establishes the minimum requirements for a two-wheel drive, conventional cab truck with a 26 foot refrigerated box. The truck will be utilized for transporting refrigerated food items on California highways with typical California ambient temperatures. The supplier is responsible for providing a truck that meets the following minimum requirements.

2 APPLICABLE SPECIFICATIONS / STANDARDS / CODES

Specifications, standards and codes referenced in this document in effect on the opening of the 'Invitation-For Bid', form a part of this specification. The vehicle furnished under these specifications shall conform to all of the requirements of all Divisions and Chapters of the following publications:

- 1. Federal Motor Vehicle Safety Standards, Federal Highway Safety and DOT.
- 2. California Motor Vehicle Code.
- 3. California Code of Regulations (i.e. Title 8, Title 13, Title 15, Title 21).
- 4. A plate identifying the manufacturer, tare weight, gross vehicle weight rating (GVWR), date of manufacture and all other information as specified in the National Traffic and Motor Vehicle Safety Act, Section 114, and Federal Code of Regulations, Title 49, shall be attached to the truck frame or body in an easily accessible location.
- 5. Federal Certification: Final stage manufacturers shall be certified by National Highway Traffic Safety Administration and be registered to manufacture or alter vehicles in accordance with the code of Federal Regulation, Title 49, Parts 567-568.
- 6. The engine shall be California Air Resource Board (CARB) certified to operate on-highway in the State of California at the time of manufacture without emission credits; and, shall meet all current Federal "Tier" emission requirements.

3 REQUIREMENTS

3.1 · GENERAL:

The vehicle shall be new and equivalent in style, quality, and appointments to those offered to the general public. The vehicle shall be supplied with all equipment and accessories indicated as standard equipment in the manufacturer's published literature. Optional equipment necessary to meet the requirements of this specification shall also be installed.

- GVWR: 26,000 pounds (maximum)
- Vehicle Height: 147 inches (maximum)

3.2 Engine:

The vehicle shall be equipped with the manufacturer's standard diesel engine that meets the following minimum requirements:

- Power: 210 hp gross (minimum)
- Torque: 560 lbs.-ft. (minimum)
- · Air cleaner, single element with restriction indicator mounted inside cab
- · Fuel water separator
- Block heater

3.3 ELECTRICAL SYSTEM:

- System Voltage: 12 Volt
- Alternator: 140 amp (minimum)
- Batteries: Maintenance free type with 1300 CCA (total, minimum)

3.4 TRANSMISSION:

The vehicle shall come equipped with the manufacturer's standard automatic transmission.

3.5 BRAKES:

Self adjusting air brakes with an Anti-lock Brake System (ABS) shall be included. Brakes shall come equipped with an air compressor capacity of 13 CFM (minimum) and include a heated air dryer.

3.6 STEERING:

Steering gear shall have either double steering boxes or a single steering box and a power assist ram.

3.7 WHEELS & TIRES:

Wheels: Six (6) hub-piloted, 10-stud, painted steel wheels with two hand holds and wheel widths as recommended by The Tire and Rim Association Inc. and the tire manufacturer shall be supplied.

Tires: Six (6) steel belted radial tubeless type tires (load range G – minimum), completely mounted and balanced on the wheels, shall be furnished. All tires supplied on this order shall be of the same make and model (Front and Rear Tires May Differ in Model), and meet the minimum GAWR.

3.8 AXLES:

Front: The front axle shall have a Gross Axle Weight Rating (GAWR) of at least 16,000 pounds.

Rear: The rear single axle shall have a GAWR of at least 19,000 pounds and have an axle ratio determined by the truck manufacturer in order to maintain a 65 MPH road speed under full load. When fully loaded, maximum weights on each axle shall not exceed the most recent State of California Vehicle Code.

3.9 FUEL TANK:

Aluminum fuel tanks with a total capacity of no less than 100 gallons.

3.10 AIR CONDITIONING:

A multi-speed cab heater, air conditioning and windshield defroster shall be included. The system shall come equipped with fresh air ventilators or combination fresh air and recirculating ventilation system

3.11 CAB:

The following items, supplementing if necessary those items already cataloged as standard cab equipment, shall be furnished and installed:

- 3.11.1 Dual visors
- 3.11.2 Dual, two-speed, windshield wipers with intermittent feature
- 3.11.3 Dual windshield washers
- 3.11.4 Instrument Cluster shall contain, at a minimum the following items:
 - Speedometer
 - · Tachometer (with redline indicator)
 - Coolant temperature
 - Engine Oil pressure
 - Fuel level.
 - · System voltage
 - Engine running time (hour meter)
- 3.11.5 Interior lights activated by opening either door and with a manual switch
- 3.11.6 Cab mounted air horns
- 3.11.7 Right and left outside rearview mirrors shall be heated with control switch inside the cab and shall be stainless steel with 102-inch wide spacing. Minimum size shall be 7" x 16"
- 3.11.8 Steps and grab handles to safely enter and exit the cab on both sides
- 3.11.9 Floor mats, headliner and full cab insulation
- 3.11.10 Driver and passenger cloth seats shall be adjustable air-ride suspension type with high back head support and dual arm rests
- 3.11.11 Seat belts for all seating positions
- 3.11.12 Interior color shall be one of the neutral colors among the manufacturer's standard colors
- 3.11.13 Three sets of keys shall be provided
- 3.11.14 All locks shall be keyed alike

3.11.15 Standard manufacturer's AM/FM/WB (Weather Band) radio, speakers and antenna

3.11.16 Adjustable tilt and telescoping steering column

3.12 CARGO BOX:

The refrigerated cargo box shall be constructed of aluminum with a minimum of 3 inches of insulation (R21 or better). Body shall be equipped with front refrigeration unit capable of keeping the box at 36° F with ambient temperature of 100° F. The cargo box shall meet the following minimum dimensions:

- \ Inside length: 25.5 feet (minimum)
- Inside width: 7.5 feet (minimum)
- inside height: 7.5 feet (minimum)

The cargo box shall include a rear roll up door with a minimum size of 87 inches wide and 82 inches high. Two rows of e-track shall be included on both sides and front of the cargo box mounted at 24 inches and 48 inches from the floor.

3.13 LIFTGATE:

The Liftgate shall come equipped with duel cart stops and meet the following minimum requirements:

- Lift Capacity: 3300 lbs.(minimum)
- Platform Depth: 84 inches (minimum)
- · Platform Width: 98 inches (minimum)

Reference model: Interlift ILK 33.

3.14 PAINT:

The cab, hood, fenders and body shall be finish painted with the manufacturer's standard white lead-free enamel paint (lead-free: 100-PPM maximum based on dry paint). The finish coat shall be free from runs, drips, sags, etc., and shall be evenly applied to provide a gloss finish. All other components shall be painted according to factory standard colors. Identification plates and labels placed on equipment and components by various manufacturers shall not be painted over.

3.15 MISCELLANEOUS:

The following miscellaneous equipment shall be furnished and installed:

- Back-up alarm, 100 dBA (minimum)
- Standard tool kit including wheel changing tools